Tel: 0086-21-32509306 Fax: 0086-21-51686997 Mob: 0086-13761409730 Email:info@medeco-medical.com

www.medeco-medical.com

http://mermaid-medical.en.made-in-china.com

### Operating lamp Operating Table Hospital Bed Manufacturer OEM service Medical Solutions



# TABLETOP AUTOCLAVE (STERILIZER) STE-18-D



### 1.Overview:

18 Liter benchtop autoclaves with class B pre-post vacuum type, complies with the European standard E N13060. With electronic door locking system. This 18 Liter autoclave are ideal for busy dental, medical, veterinarian, beauty and laboratory purposes.

### 2. Excellent Performance:

- . Full automatic table top autoclave with pre set programs.
- . Complies with European standard EN13060.
- . In built independent rapid steam generator ensures quick sterilization cycles.
- . Rapid post sterilization vacuum drying.
- . User friendly interface.
- . LCD screen displaying time, temperature and pressure, process alert and instrument conditions.
- . Choice of language setting including: English, Spanish, German, Polish, French, Hungarian, Romanian, Dutch, Lithuanian, Lavian, Czech, Italian and Chinese.
- . Easily accessible watertank.
- 3. Safety and Monitoring:
- . Double door protection system prevents the cycle from starting if the door is not correctly locked. This s ystem also prevents the door from opening if the pressure inside the chamber is not equal to atmospheric pressure outside the chamber.
- . Pressure safety valve prevents over pressure in the chamber and steam generator.
- . The power is automatically cut if a short circuit or electrical fault occurs.
- . Able to detect and identify the exact cause of any problem, and to issue a specific error code to the opera tor.
- . Water level main switch in the main tank controlling the min and max water level.
- . Automatic warning for maintenance.

## 4. Documentation:

No.222 Meidan Road Shanghai, China.201908 Tel: 0086-21-32509306 Fax: 0086-21-51686997 Mob: 0086-13761409730 Email:info@medeco-medical.com

www.medeco-medical.com

http://mermaid-medical.en.made-in-china.com





- . Printer (option): an internal printer is optional.
- . USB port (option): it is used for connecting a USB stick, all sterilization data are automatically written in the USB stick, and can be ready directly in any PC and stored electronically.
- . Internal Memory: the last 20 cycles can be automatically stored in the autoclave system, which can be pr inted out at any time.

### 1.Parameter

Chamber Dimension (mm)	Ø247x350			
Chamber Volume (Liter)	23			
Number of Trays	3			
Voltage (V) Freq. (Hz)	220/110V, 50/60Hz			
Power (W)	2200			
Overall Dimension (WxHxD,mm)	480x455x600			
Autoclave Weight (Kgs)	51			

#### 2.Programmed cycle

Z.Programmed cycle					
Program	TEMP.	Pressure	Sterilization Time (min)	Total Time (min)	
	(℃)	(Mpa)			
SOLID	134	210	4	15-25	
	121	110	20	25-40	
LIQUID	134	210	10	25-50	
	121	110	30	30-55	
WRAPPED	134	210	10	20-45	
	121	110	30	30-50	
TEXTILE	134	210	10	20-45	
	121	110	30	30-50	
PRION	134	210	18	30-50	
DRYING	/	/	/	1-20	
B&D TEST	134	210	3.5	22-35	
HELIX TEST	134	210	3.5	22-35	
VACUUM TEST	/	/	/	15-20	

Remark: The "DRYING" program is option, if choose this program, it will instead of "TEXTILE" program.



