MEDECO Shanghai Medeco Industry Co.,Ltd. No.222 Meidan Road Shanghai, China.201908 Tel: 0086-21-32509306 Fax: 0086-21-51686997 Mob: 0086-13761409730 Email:info@medeco-medical.com www.medeco-medical.com http://mermaid-medical.en.made-in-china.com

Operating lamp Operating Table Hospital Bed Manufacturer OEM service Medical Solutions



## TABLETOP AUTOCLAVE (STERILIZER) STE-23-C



## 1. Overview:

23 Liter benchtop autoclaves with class B pre-post vacuum type, complies with the European standard E N13060. This 23Liter autoclave are ideal for busy dental, medical, veterinarian, beauty and laboratory pur poses.

2.Excellent Performance:

- . Full automatic table top autoclave with pre set programs.
- . Complies with European standard EN13060.
- . In built independent rapid steam generator ensures quick sterilization cycles.
- . Rapid post sterilization vacuum drying.
- . User friendly interface.

. LCD screen displaying time, temperature and pressure, process alert and instrument conditions.

. Choice of language setting including: English, Spanish, German, Polish, French, Hungarian, Romanian,

Dutch, Lithuanian, Lavian, Czech, Italian and Chinese.

. Easily accessible watertank.

3.Safety and Monitoring :

. Double door protection system prevents the cycle from starting if the door is not correctly locked. This s ystem also prevents the door from opening if the pressure inside the chamber is not equal to atmospheric pressure outside the chamber.

- . Pressure safety valve prevents over pressure in the chamber and steam generator.
- . The power is automatically cut if a short circuit or electrical fault occurs.

. Able to detect and identify the exact cause of any problem, and to issue a specific error code to the opera tor.

- . Water level main switch in the main tank controlling the min and max water level.
- . Automatic warning for maintenance.

4.Documentation:



. Printer (option): an external printer is optional for all "icanclave" autoclaves.

. USB port (option): it is used for connecting a USB stick, all sterilization data are automatically written i n the USB stick, and can be ready directly in any PC and stored electronically.

. Internal Memory: the last 20 cycles can be automatically stored in the autoclave system, which can be pr inted out at any time.

_		
$\mathbf{P}$	arameter	•
•1	arameter	

Chamber Dimension (mm)	Ø247x450
Chamber Volume (Liter)	23
Number of Trays	3
Voltage (V) Freq. (Hz)	220/110V, 50/60Hz
Power (W)	2200
Overall Dimension (WxHxD,mm)	480x465x690
Autoclave Weight (Kgs)	51

## 2.Programmed cycle

Program	TEMP.	Pressure	Sterilization Time (min)	Total Time (min)
	(°C)	(Mpa)		
SOLID	134	210	4	15-25
	121	110	20	25-40
LIQUID	134	210	10	25-50
	121	110	30	30-55
WRAPPED	134	210	10	20-45
	121	110	30	30-50
TEXTILE	134	210	10	20-45
	121	110	30	30-50
PRION	134	210	18	30-50
DRYING	/	/	/	1-20
B&D TEST	134	210	3.5	22-35
HELIX TEST	134	210	3.5	22-35
VACUUM TEST	/	/	/	15-20

Remark: The "DRYING" program is option, if choose this program, it will instead of "TEXTILE" program.



